

JB4PLUS

"JB4PLUS": SCATOLA DI GIUNZIONE EQUALIZZATA CON PROTEZIONE CONTRO SOVRATENSIONI, FINO A 4 CELLE DI CARICO



Scatola di giunzione IP67 a 4 ingressi specifica per ambienti esterni, permette di essere utilizzata come scatola di equalizzazione o di giunzione semplice di 2, 3 o 4 celle di carico. Morsettiere a vite per agevolare il collegamento e trimmer di regolazione del segnale, per una equalizzazione precisa ed affidabile. Il circuito di protezione protegge contro fulmini e sovratensioni.

La soluzione ideale per
applicazioni industriali
avanzate

CARATTERISTICHE TECNICHE

- Involucro in ABS. Grado di protezione: IP67.
- Massima tensione in ingresso: 5Vdc.
- Massima corrente in ingresso: 700mA.
- Massimo segnale cella in ingresso: 1000mV.
- Corrente di impulso di picco: 15kA.
- Effetto della temperatura: 50ppm/°C.
- Dimensioni (lxwxh): 120x80x55mm.



“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE